

STEEL SECURITY PATIO DOOR






PRODUCT MEASURING GUIDE

VIEW INSTALLATION VIDEOS AT helpmeinstallit.com


1 Determine Mounting Method and Rough Opening Measuring Points

The security door will require a minimum mounting surface of 1" on the trim above and on both sides of the sliding patio door. Mounting screws must be secured to a stud in the wall. Review **Figures 1-5** to determine which mounting method you can and wish to use and the rough opening measurement.

Door is mounted with projection brackets that project 3" from mounting surface.




2 Determine Door Swing



RIGHT ACTIVE
Door on the right will be used

Left or Right?
Determine active door as viewed from outside (see illustrations)
Note: all doors are reversible



LEFT ACTIVE
Door on the left will be used

5 Measure & Record Rough Opening

Height

Measure the height, right, left and center from the bottom edge of the mounting surface to the existing threshold of your entry door.

Use the **SMALLEST** of the 3 measurements if they vary.

H1 ____ **H2** ____ **H3** ____

Record door height

Width

Measure the top, middle and the bottom of the door opening across the existing entry door frame from mounting surface inside edge to mounting surface inside edge.

Use the **SMALLEST** of the 3 measurements if they vary.

W1 ____ **W2** ____ **W3** ____

Record door width





Height

Record smallest measurement



Width

Record smallest measurement



6 Determine Which Doors & Sizes Will Fit

Once you have measured for height and width, use the following charts to determine which models and sizes will fit in your opening. If your opening height and width measurements are within the Rough Opening Fit Range listed for the size and model in question, that Call Size will fit your opening when properly installed. If you have an unusual size opening and none of the models and standard sizes listed will fit, see a Home Depot associate to review your custom size security door options in the MyCD system.

Model	Call Size	Rough Opening* Fit Range	Frame Size	Tab Size (tip to tip)	Call Size	Rough Opening Fit* Range	Frame Size	Tab Size (tip to tip)
Width					Height			
Castleguard	72"	68-1/4" - 75-1/4"	73-1/4"	77-1/4"	80"	78-5/8" - 82"	80"	84"
Castleguard MAX	72"	68-1/4" - 75-1/4"	73-1/4"	77-1/4"	80"	78-5/8" - 82"	80"	84"
Safeguard	60"	56-1/4" - 63-1/4"	61-1/4"	65-1/4"	80"	78-5/8" - 82"	80"	84"
	72"	68-1/4" - 75-1/4"	73-1/4"	77-1/4"	80"	78-5/8" - 82"	80"	84"
	96"	92-1/4" - 99-1/4"	97-1/4"	101-1/4"	80"	78-5/8" - 82"	80"	84"
CUSTOM SIZES AVAILABLE					CUSTOM SIZES AVAILABLE			

* Rough opening fit range can be larger than frame size because mounting brackets project an additional 2" on each side of the frame. Be sure there are not obstructions within 3" (including the frame) on either side of the rough opening.

